

FOLIA IKONOS BRICK STICK

-----Technical Data Sheet -----

Description: Premium quality rough wall sticker, glossy polymeric white soft PVC film with transparent adhesive. Offered with a liner of single-side PE-coated paper.

Surface: 90±10um polymeric white soft PVC film.

Adhesive: 40±5um transparent adhesive-permanent.

Liner: 140±5gsm single-side PE-coated white wood-pulp paper.

Warranty: 1 year after production.

Compatible Ink: UV Ink/ Eco Solvent Ink/ HP Latex Inks.

Features: With polymeric white PVC film, I-1015 is more flexible which can be perfectly attached to the substrates with heat gun.

Applications: Widely used for rough wall graphics.

Size: 1.27/ 1.37 *50M

Physical Characteristics:

Characteristics	Test Method	Typical Value
Surface Thickness	ZC/QR08	0.090MM ± 0.010MM
Adhesive Thickness	ZC/QR08	0.040MM ± 0.005MM
Liner Thickness	ZC/QR08	0.160MM ± 0.010MM
Surface brightness	ZC/QR08	60-85GS
	Tested by D60 standard Photometric apparatus;	
Adhesive Force	ZC/QR08	2.2kg/inch ± 18%
Release Force	ZC/QR08	0.019± 0.005 kg/inch
Initial Tack	20Minutes in the standard lab	Ball No.5
Test Temperature		25±2℃, 65%±15%RH
Application Temperature		10℃-35℃ 30%-70%RH
Storage Temperature		10℃-35℃ 30%-70%RH