

## FOLIA IKONOS PROFIFLEX COLOR

For medium term indoor and outdoor applications.

|       |                                               |
|-------|-----------------------------------------------|
| FILM  | Colored, matt                                 |
| LINER | Siliconised CCK 140 gr/m2                     |
| GLUE  | Acrylic, gray colored, water based, permanent |
| APPLY | All kind of outdoor and indoor applications   |

|                                                   | TEST METHOD | UNIT    | VALUE | TOLEANCE     |
|---------------------------------------------------|-------------|---------|-------|--------------|
| -THICKNESS                                        | ASTM D 1593 | µm      | 70    | ±10%         |
| -TENSILE STRENGHT<br>)MD<br>><br>)TD              | ASTM D 882  | Mpa     |       | ≥ 35<br>≥ 28 |
| -ELONGATION AT BREAK<br>)MD<br>><br>)TD           | ASTM D 882  | %<br>%  |       | >200<br>>200 |
| -DIMENSIONAL STABILITY ><br>10 min -70 ° C<br>)TD | ASTM 1204   | %<br>%  |       | -4 max<br>±1 |
| -GLOSS 60 °                                       | ASTM 523    | G.U.    |       | ≤ 20         |
| -SURFACE TENSION                                  | ASTM D 2578 | Dyne/cm |       | ≥ 36         |

