



FILMS DÉCORATIFS

INT 520 BLACKOUT PATTERN

INDOOR INSTALLATION



BROKEN GLASS EFFECT

DESCRIPTION

Decorative films allow you to personalize a window or a piece of glass furniture while preserving privacy. These films soften the light without reducing the brightness and bring a touch of originality in the decoration of your projects.



Durability: 12 to 15 years for a vertical application in Central Europe.



Use: for all types of glass.



Maintenance : after 30 days with a usual cleaning solution (non abrasive, without ammonia...). Cleaning products that could scratch are not recommended.



Storage: 2 years from delivery. This film must be stored away from excessive humidity and sunlight, at a temperature below 38°C.

In order to meet high standards, we recommend that you do not mix films from different productions

INFORMATION

MATERIAL :.....PET
ADHESIVE :.....Acrylic polymer 13 gr/m²
LINER :.....Siliconized PET 23 microns
THICKNESS :.....23 microns
COLOR :.....Incolor
APPLICATION SIDE :.....Internal
APPLICATION T° :.....min, + 5°C
STANDARDS :.....EUROCLASSES
FIRE RANTING :.....B-s1,d0
GUARANTEE :.....10 Years inside*

* For glazing not exposed to the sun

DIMENSIONS

By roll :



1,52 x

10 m
30 m

Application
Note



Video of the
installation



Method of application

The surface to be bonded must be free of dust, grease or any other contaminant. Some materials such as polycarbonate can cause bubbling problems. A compatibility test is therefore recommended. Possibility to install on plexiglass and polycarbonate.

Production monitoring and standards

In order to constantly improve our productions, we may have to modify without notice the colors and manufacturing processes. We recommend to our users, before applying our films, to make sure that they are exactly suitable for the intended use and to comply with the standards in force.